

*制御電源 ±15V仕様

形 (Type)	名	HC-PDG05V4B15	HC-PDG10V4B15	HC-PDG15V4B15	HC-PDG20V4B15	HC-PDG25V4B15
定格電流 [If] (Rated current)	±5A	±10A	±15A	±20A	±25A	
連続通電DC電流 (Continuously flowing DC current)	±8.8A	±13.8A	±23.3A	±23.3A	±23.3A	
飽和電流 [Is] (Saturation current)	±15A	±25A	±37.5A	±50A	±75A	
直線性範囲 (Linearity limits)	0~±13.5A	0~±22.5A	0~±33.75A	0~±45A	0~±67.5A	
1次巻線線径 (Size of primary winding)	ϕ 0.8	ϕ 1.0	ϕ 1.3	ϕ 1.3	ϕ 1.3	
ターン数 (Turns)	10	6	4	3	2	
定格出力 [Vh] (Rated output)			±4V±1.5% (RL=10kΩ)			
残留出力 [VO] (Residual output)			Within ±50mV			
直線性 (Output linearity)			Within ±1%			
応答速度 (Response time)			Within 10 μs (at di/dt=If/ μs)			
過渡特性 (Response performance)			Within 10%			
ヒステリシス巾 (Hysteresis Voltage range)			Within 60mV			
出力温度特性 (Output Temp. Coef.)			Within ±0.1%/°C			
残留出力温度特性 (Residual output Temp. Coef.)			Within ±2mV/°C			
制御電源 (Control power supply)			±15V±5%			
消費電流 (Consumption current)			Within 20mA			
使用温度範囲 (Operating Temp.)			-10°C~+80°C			
保存温度範囲 (Strage Temp.)			-15°C~+85°C			
耐電圧 (Dielectric withstand voltage)			2500V AC 50/60Hz 1minute			
絶縁抵抗 (Insulation resistance)			Not less than 500MΩ 500V DC			

*制御電源 ±15V仕様

形 名 (Type)	HC-PDG30V4B15	HC-PDG35V4B15	HC-PDG40V4B15	HC-PDG45V4B15	HC-PDG50V4B15
定格電流 [If] (Rated current)	±30A	±35A	±40A	±45A	±50A
連続通電DC電流 (Continuously flowing DC current)	±23.3A	±23.3A	±35.4A	±35.4A	±35.4A
飽和電流 [Is] (Saturation current)	±75A	±75A	±120A	±135A	±150A
直線性範囲 (Linearity limits)	0~±67.5A	0~±67.5A	0~±120A	0~±135A	0~±135A
1次巻線線径 (Size of primary winding)	ϕ 1.3	ϕ 1.3	ϕ 1.6	ϕ 1.6	ϕ 1.6
ターン数 (Turns)	2	2	1	1	1
定格出力 [Vh] (Rated output)	±4V±1.5% (RL=10kΩ)				
残留出力 [VO] (Residual output)	Within ±50mV				
直線性 (Output linearity)	Within ±1%				
応答速度 (Response time)	Within 10 μs (at di/dt=If/ μs)				
過渡特性 (Response performance)	Within 10%				
ヒステリシス巾 (Hysteresis Voltage range)	Within 60mV				
出力温度特性 (Output Temp. Coef.)	Within ±0.1%/°C				
残留出力温度特性 (Residual output Temp. Coef.)	Within ±2mV/°C				
制御電源 (Control power supply)	±15V±5%				
消費電流 (Consumption current)	Within 20mA				
使用温度範囲 (Operating Temp.)	-10°C~+80°C				
保存温度範囲 (Storage Temp.)	-15°C~+85°C				
耐電圧 (Dielectric withstand voltage)	2500V AC 50/60Hz 1minute				
絶縁抵抗 (Insulation resistance)	Not less than 500MΩ 500V DC				